

In-Line Transit-Time Ultrasonic Flow Meter

Features

- Accuracy +/- 0.5% of reading
- Repeatability +/- 0.5% of reading
- Ultrasonic Flow meter for the detection of the flow rate of most liquids
- Ultra-precise patented time measurement technology measures the transit-time accurately between the upstream and downstream transducers
- Excellent zero tracking with no damping; will measure down to zero flow
- Powder Coated Carbon Steel (150# ANSI or DN PN 10)
- NEMA 4X (IP65) die cast PC/ABS enclosure
- Power: 90 to 250 VAC, 48 to 63 Hz and 10 to 36 VDC
- Outputs: OCT pulse (1 Hz to 1 KHz); 0/4 to 20mA DC (500 Ohm max); Relay (on/off time <2 m sec, max current load 1.2 amps); RS-232
- Wide operating temperature range for measured fluid -40F to 176F (-40C to 80C)
- Wide bi-directional flow range of 0 to 23 ft/s liquids (0 to 7 m/s)
- In-line body sizes from 1.0" to 10" (25mm-250mm)

SIERRA[®]
INSTRUMENTS
THE MASS FLOW COMPANY

ISO
REGISTERED
9001

For information online...
www.sierrainstruments.com

Innova-Sonic[®] Model 206 In-Line



Description

Our Innova-Sonic[®] Model 206 In-Line is a state-of-the-art digital correlation transit-time ultrasonic flow meter designed to give the end-user high performance at an affordable price. The instrument is designed specifically as an alternative choice or replacement for magnetic flow meter applications. The instrument is also an ideal choice for any liquid flow application found in general industry and has been assessed by the American Bureau of Shipping (ABS) for shipboard use.

While principally designed for clean liquid applications, our Innova-Sonic In-Line is tolerant of liquids with small amounts of air bubbles or suspended solids common in most industrial environments. All flow meters in Sierra's Innova-Sonic family offer low power consumption, high reliability and outstanding applicability at an affordable price.

Our Innova-Sonic In-line is an order-of-magnitude improvement in transit-time ultrasonic flow meters and features our patented ultra-precise PicoFly™ measurement technology. An industry first, this advanced technology allows ultrasonic transit time-of-flight samples to be measured in picoseconds 10^{-12} (one trillionth of a second) for superb resolution and tremendous low flow detection rather than the typical nanoseconds 10^{-9} (one billionth of a second). In fact, the Innova-Sonic In-Line can read zero and track zero flow with no damping.

The Model 206 is designed specifically to offer an alternative choice or replacement for magnetic flow meter applications. The instrument is also an ideal choice for any liquid flow application found in general industry.

The chart below shows how our Innova-Sonic® compared to a typical industrial Magnetic Flow Meter.

	Magnetic Flow Meters	Innova-Sonic® Model 206 In-Line Flow Meter
Accuracy	+/- 0.5% to +/- 1.0% of reading	+/-0.5% of reading
Turndown	Down to approx. 0.1 fps	Measure down to ZERO flow due to patented PicoFly™ technology
Applicability	Conductive Liquids Only. Cannot measure hydrocarbons, distilled water or many non-aqueous solutions	Any clean liquid. Can tolerate small amounts of suspended solids and air bubbles
Economy	Medium cost. Coriolis much higher cost, Turbine meters lower cost	Somewhat lower cost... Price comparable to high-end turbine meters, yet with higher accuracy and less maintenance (no moving parts)

Performance Specifications

Flow range

0 to +/- 23 ft/s (0 to +/- 7 m/s)

Accuracy

+/- 0.5% of reading

Repeatability

+/- 0.5% of reading

In Line flow body size

1.0 in to 10 in (25mm to 250mm), 150# ANSI or DN PN 10 Flanges




Figure above shows the much quicker response of the Innova-Sonic® (yellow line) as compared to a mag meter (red line) during a step change in flow.

Operating Specifications

Outputs

Analog: 0/4 to 20mA, DC . Max load 500 ohms

RS-232

OCT Pulse Output: 1 to 1000 Hz

Relay: On-off time <2 milliseconds, max current load 1.2A

Power supply

90 to 250 VAC, 48 to 63 Hz and 12 to 36 VDC

Keypad Programming

16 key 4 x 4 touch keypad on front of enclosure

Display

20 character, 2 line (20x2) alphanumeric, backlit LCD

Temperature

Fluid: -40C to 80C (-40F to 176F)

Physical Specifications



Transmitter

NEMA 4x (IP65), Die cast PC/ABS Enclosure

Transducer

Spool piece with wetted transducers NEMA6P (IP68), pressure rating 150 psig (10 barg).

Pipe size DN (inches)	Dimensions (inches)		
	L	H	W
25 (1")	400 (15")	120 (4.8")	180 (7.2")
40 (1.5")	450 (18")	135 (5.4")	200 (8")
50 (2")	500 (20")	150 (6")	210 (8.4")
65 (2.5")	400(16")	230 (9.2")	165 (6.6")
80 (3.0")	400 (16")	245 (9.8")	190 (7.6")
100 (4")	400 (16")	265 (10.6")	215 (8.6")
150 (6")	450 (18")	315 (12.6")	280 (11.2")
200 (8")	550 (22")	365 (14.6")	335 (13.4")
250 (10")	600 (24")	415 (16.6")	405 (16.2")



Ordering the Model 206

PARENT MODEL NUMBER

206 In-line Ultrasonic Flow meter

Velocity range: +/- 0 to 22 ft/s (0 to 7m/s), Accuracy: +/- 0.5% of reading;
 Repeatability: +/- 0.07% of reading; Pipe size: 1.0" to 10" (25 to 250mm); coated
 carbon steel body with 150# ANSI or DN PN10 Flange; In-Line transducer -40F
 to 176F (-40C to 80C); 10 to 36V DC or 90 to 250 VAC, 48 to 63 Hz. OCT Pulse
 output, 0/4 to 20mA, Relay; RS-232; IP65, die-cast PC/ABS 16 (8 x 2) Keyboard;
 20 x 2 alphanumeric backlit display

206

FLOW BODY

25 Carbon Steel Body with 150# ANSI Flanges
 In-Line transducer -40F to 176F (-40C to 80C); Pipe Size 1.0" (25)

40 Carbon Steel Body with 150# ANSI Flanges
 In-Line transducer -40F to 176F (-40C to 80C); Pipe Size 1.5" (40)

50 Carbon Steel Body with 150# ANSI Flanges
 In-Line transducer -40F to 176F (-40C to 80C); Pipe Size 2.0" (50)

65 Carbon Steel Body with 150# ANSI Flanges
 In-Line transducer -40F to 176F (-40C to 80C); Pipe Size 2.5" (65)

80 Carbon Steel Body with 150# ANSI Flanges
 In-Line transducer -40F to 176F (-40C to 80C); Pipe Size 3.0" (75)

100 Carbon Steel Body with 150# ANSI Flanges
 In-Line transducer -40F to 176F (-40C to 80C); Pipe Size 4.0" (100)

150 Carbon Steel Body with 150# ANSI Flanges
 In-Line transducer -40F to 176F (-40C to 80C); Pipe Size 6.0" (150)

200 Carbon Steel Body with 150# ANSI Flanges
 In-Line transducer -40F to 176F (-40C to 80C); Pipe Size 8.0" (200)

250 Carbon Steel Body with 150# ANSI Flanges
 In-Line transducer -40F to 176F (-40C to 80C); Pipe Size 10.0" (250)

**Note: To order DN PN 10 flange, add "D" to flow body code:
 ex: D25**

CABLE LENGTH

30 30 ft (9m) standard cable length

50 50 ft (15m)

100 100 ft (30m)

150 150 ft (45m)

200 30 ft (60m)

300 300 ft (90m)

OPTION: NIST TRACEABLE

NIST 5 Point Calibration Certification traceable to NIST

□ □ □



Innova-Sonic® Model 205 Clamp-on Liquid Flow Meter

Non-invasive transit-time ultrasonic digital flow meter for the detection of the flow rate of most liquids.



Innova-Sonic® Model 205 Insertion Liquid Flow Meter

A transit-time ultrasonic digital flow meter featuring insertion transducers that can be used on pipe sizes ranging from 2" to 400" (50mm to 10000mm). The key benefit is the high signal strength achieved by using insertion transducers so that pipe wall, pipe liner, and pipe wall deposits do not affect instrument performance.



Innova-Sonic® Model 206 In-Line Liquid Flow Meter

A state-of-the-art digital correlation transit-time ultrasonic flow meter featuring PicoFly™ technology and designed to give customers an alternative choice for typical liquid Mag-Meter applications. Featuring +/- 0.5% of reading accuracy and the ability to measure down to zero flow in virtually any clean liquid regardless of conductivity.



Innova-Sonic® Model 210 Portable Liquid Flow Meter with Bluetooth® Wireless

A non-invasive portable transit-time ultrasonic flow meter for the detection of the volumetric flow rate of most liquids. A PDA is used to operate and read data using Bluetooth® wireless connectivity.



SIERRA INSTRUMENTS, NORTH AMERICA • 5 Harris Court, Building L • Monterey, California • (800) 866-0200 • (831) 373-0200 • Fax (831) 373-4402 • www.sierrainstruments.com

SIERRA INSTRUMENTS, EUROPE • Bijlmansweid 2 • 1934RE Egmond aan den Hoef • The Netherlands • +31 72 5071400 • Fax: +31 72 5071401

SIERRA INSTRUMENTS, ASIA • Rm.618, Tomson Centre, Bldg. A • 188 Zhang Yang Road • Pu Dong New District • Shanghai, P.R. China 200122 • +8621 5879 8522 • Fax: +8621 5879 8586